

FLOS

Camouflage 140 - Specification Sheet by Piero Lissoni, 2017

Mounting	Wall
Lamp (Bulb) Description	8W, 786lm, 2700K, CRI80
Environment	Outdoor - Wet location
Dimming	No dimmable
Finish	White
Technical and Product Description	"Recommended connections for in-ground installations with a 2-way terminal block 4-pole IP68 water stop on 24V side. Order separately (by others) All drivers should be installed in weather resistant enclosures (by others) or indoors. Silicon filled wire-nuts, should be used on all line-voltage connections to avoid syphoning moisture to electrical components. Stone finishes are a fiberglass reinforced cement mixture. The primer version is suitable for paint after installation with any water-based exterior paint or stucco. The painted versions are an exterior rated epoxy polyester powder coat finish for superior strength, heat and UV resistance. During installation and maintenance avoid scratching or damaging the finish as it may result in premature corrosion of metal surfaces. Avoid cleaning fixtures with corrosive chemicals as it may result in voiding the warranty. LED fixtures are highly susceptible to failure due to electrical effects from poor connections, and electrical short circuits. These are frequently caused by (a) over-voltage from primary voltage sources, (b) electrostatic discharge from the exterior environment. Ensure that all outdoor fixtures are installed on GFI circuits as required by code, and use proper surge protecting devices to avoid irreversible damages to electrical components."

Electrical

Voltage	120-277
IP Rating	IP65


Physical

Construction Material	Aluminum / Stone
Weight	1.76 lbs



F1310U01-24V White

Dimensional Image



CAMOUFLAGE
140MM / 5.5 IN

Certifications

