

m o o o i

Perch Light Wall

UMUT YAMAC



Made of folded paper and brass, the Perch evokes a feeling of freedom. Let the graceful bird swing and glow with joy. Just beware that it might just spread its wings and fly away...

Detailing




This sunlit bird is free to swing when softly touched. It gently glows and brings along the promise of spring.

Colours

Brass and white

Perch Light Wall / Large non-dimmable

Dimensions



Product

WIDTH 33cm | 13"
HEIGHT 51cm | 20.1"
DEPTH 18cm | 7.1"
WEIGHT NETTO 3kg | 6.61lbs

Packaging

WIDTH 34cm | 13.4"
HEIGHT 21cm | 8.3"
CUBAGE 0.06m³ | 2.09ft³
LENGTH 83cm | 32.7"
WEIGHT 2.5kg | 5.51lbs

Technical CE

MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENERGY LABEL

Energy Label B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

90-264

FREQUENCY

50/60

MAX POWER CONSUMPTION

5W

DIMMABLE

No

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

260cm | 102.4"

COLOUR TEMPERATURE

3000 K

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

150 lm

Technical cULus

MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

DIMMABLE

No

LIFETIME

50000 hours

CRI

80

LIGHT OUTPUT

150 lm

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

100-240

MAX POWER CONSUMPTION

5W

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

3000 K

LIGHT DIRECTION

All directions

Perch Light Wall / Recessed Large dimmable 1-10V

Dimensions

8cm | 2.8"



15cm | 5.9"

33cm | 13"



51cm | 20.1"

Product

WIDTH 33cm | 13"

HEIGHT 51cm | 20.1"

DEPTH 15cm | 5.9"

WEIGHT NETTO 2kg | 4.4lbs

Packaging

WIDTH 34cm | 13.4"

HEIGHT 15cm | 5.9"

CUBAGE 0.04m³ | 1.26ft³

LENGTH 70cm | 27.6"

WEIGHT 2kg | 4.4lbs

*Technical CE***MATERIAL**

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENERGY LABEL

Energy Label B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR TEMPERATURE

3000 K

LIGHT OUTPUT

150 lm

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

180-240

MAX POWER CONSUMPTION

5W

LIFETIME


50000 hours

CRI

80

Perch Light Wall / Recessed Small dimmable 1-10V

Dimensions



Product

WIDTH 25cm | 9.8"
HEIGHT 41cm | 16.1"
DEPTH 15cm | 5.9"
WEIGHT NETTO 2kg | 4.4lbs

Packaging

WIDTH 34cm | 13.4"
HEIGHT 15cm | 5.9"
CUBAGE 0.04m³ | 1.26ft³
LENGTH 70cm | 27.6"
WEIGHT 2kg | 4.4lbs

Technical CE

MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENERGY LABEL

Energy Label B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

180-240

FREQUENCY

50/60

MAX POWER CONSUMPTION

5W

DIMMABLE

Yes

COLOUR TEMPERATURE

3000 K

LIGHT OUTPUT

150 lm

LIFETIME


50000 hours

CRI

80

Perch Light Wall / Small non-dimmable

Dimensions



Product

WIDTH 25cm | 9.8"**HEIGHT** 41cm | 16.1"**DEPTH** 18cm | 7.1"**WEIGHT NETTO** 3kg | 6.61lbs

Packaging

WIDTH 34cm | 13.4"**HEIGHT** 21cm | 8.3"**CUBAGE** 0.06m³ | 2.09ft³**LENGTH** 83cm | 32.7"**WEIGHT** 2.5kg | 5.51lbs

Technical CE

MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENERGY LABEL

Energy Label B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

90-264

FREQUENCY

50/60

MAX POWER CONSUMPTION

5W

DIMMABLE

No

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

260cm | 102.4"

COLOUR TEMPERATURE

3000 K

CRI

80

LIGHT OUTPUT

90 lm

*Technical cULus***MATERIAL**

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENERGY LABEL

Energy Label B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

100-240

FREQUENCY

50/60

MAX POWER CONSUMPTION

5W

DIMMABLE

No

LIFETIME

50000 hours

COLOUR TEMPERATURE

3000 K

CRI

80

LIGHT OUTPUT

90 lm
